



Product Features

- PUSH Dimming (Push one time to turn on and turn off the light, push long time to dim the light be bright or dark).
- Selectable constant current and constant voltage output. (Custom on request)
- Full-isolated, delivering up to 60W of power.
- Short circuit, over current and over voltage protection. Up to 80% efficient.
- Fireproof environmental protection PC plastic cover
- 2 years quality warranty



Technical Specifications

Model No.	PU-CV-60			
Input Voltage Range	90-130V&180-240V/AC			
AC Frequency	48-62Hz			
Input current	0.78Amax			
Output Mode	Constant Voltage			
Output Current	4000mA	2500mA	1700mA	1200mA
On Load Voltage	12V	24V	36V	48V
No Load Voltage	12V	24V	36V	48V
Output Power	60W Max.			
Power Factor	>0.95			
Efficiency	>80%			
Dimensions	154.6*49.5*40.5(mm)			
Weight	225g			

Environmental Specifications

Operating Temperature	-30~45°C
Storage Temperature	-40~+70°C
Thermal Dissipation	Nature
Relative Humidity	5~95%
Isolation Voltage	In/Out 3750VAC
Vibration	5-55Hz/2g, 30 Minutes
Life Time	50000Hours, at TC max

Conformity & Standards

EMI	EN55022 EN55015 Class B
Safety	EN60598
Electromagnetic Immunity	EN61547, EN5024 EN61000-4-2/3/4/6/8/11
Harmonic Current Emissions	EN61000-3-2 EN61000-3-3